

LTP Series

LTP1245 PRINTER

The LTP1245 is a thermal line printer that offers high-speed, high-resolution printing in a compact, lightweight mechanism ideal for today's 5V portable applications. Providing low-power consumption to support battery-powered operation, the LTP1245 is a maintenance-free mechanism and, with optional interface, allows for automatic paper loading. Ideal for measuring instruments, analyzers, POS, portable communications devices and more, the LTP1245 maximizes printer functionality in applications where minimizing power consumption, size and weight is a priority.

- High resolution printing (8 dots/mm)
- High speed, low voltage printing (25mm @ 5V, 62.5mm @ 8.0V)
- Low 4.2V to 8.5V power supply operation
- Prints on label stock
- Available with or without paper feed knob
- Available with straight or curved paper path (up to 95 μ m)
- Thick paper printing possible on straight path
- Automatic paper loading (available with IF1001-01B interface board)
- Wide opening head for easy access
- Wide temperature range

如需要更详细的PDF或参数，请联系我们，或E-MAIL给我公司

QQ905052812

MSN: sz_lkj@hotmail.com



For a more detailed PDF or parameters, please contact us or to our E-MAIL

LTP1245-384-E
LTP1245H-384
LTP1245F-C384
LTP1245S-C384-E
LTP1245V-C384-E
LTP1245U-S384-E
LTP1245M-C384
LTP1245R-C384-E
LTP1245P-S384
LTP1245K-C384
LTP1245E-384A
LTP1245H-384
LTP1245N-S384
LTP1245T-S384-E

Model		LTP1245
Printing	Method	Thermal line dot system
	No. of dots/line	384
	No. of characters/line	24
	Width (mm)	48
	Resolution	8 dots/mm
	Paper feed pitch (mm)	0.125
	Speed (mm/s)	25 @ 5V, 62.5 @ 8.0V
Detection	Speed (cl/s)	7.5 @ 5V, 12.5 @ 8.0V
	Head temperature	By thermistor
	Paper out detection	By photo interrupter
	Head up detection	By photo interrupter
Dimensions (WxDxH) mm		72 X 39.5 X 16
Weight (g)		45
Power supply	Operating voltage	4.2 V to 8.5 V
	Current consumption	2.1 Max. @ 5 VDC, 3.3 Max. @ 8.0 VDC 64 dots
Service life	Pulse activation	min. 100 million pulses (12.5% print ratio)
	Abrasion resistance	50km or more
Operating temperature (°C)		-30 to +70 (wide temperature range)
Storage temperature (°C)		-35 to +75
Paper	Width (mm)	58 +0/-1
	Path	Straight or curve
	Thickness (μ m)	65 \pm 5
Auto cutter		ACU6205 Optional

Thermal Printers

深圳市郁金香电子-微型打印机芯，微型打印组件，配件
深圳市福田区郁金香电子经营部

printer mechanism 打印机芯

门市部：深圳市福田区中航路都会100电子商城4楼4C113

电话TEL：+86 755 83662036

传真Fax：+86 755 22638877

Tel：(+86)0755-83956982

83662036

Fax：(+86) (0755) 22

手机：13798497616

MSN: sz_lkj@hotmail.com

ACU6205A/B AUTO CUTTER

The ACU6205 is a compact and lightweight circular cut type automatic cutter developed for the LTP1245 thermal line printer mechanism.

- Full cut and partial cut are available
- Easily mounts on printer mechanism, opens for easy maintenance



ACU6205

IF1001-01B INTERFACE BOARD FOR LTP1245 SERIES

The IF1001-01B is an interface board used specifically for the LTP1245 Series. It is equipped with 8-bit parallel and serial TTL data input terminals. The IF1001-01B brings its printing functions into full play using a wide variety of characters and function commands.

PT100P01/PT101P01 AND PT120P01 CPU FOR LTP1245 SERIES

- Prints with less current using dynamic division control in accordance with the number of dots to be activated
- Supports both parallel and serial input
- Ensures high-quality print by measuring the temperature and voltage, and adjusting the print density
- Provides a wide variety of user-defined character functions including double-width/double-height, inverse print, underlining, and character spacing control; character string
- Supports bit image graphics and characters
- Provides a ruler line function which enables ruler lines and characters to be easily superimposed
- Stamp function

Model	IF1001-01B
Applicable mechanism	All LTP1245 Series
CPU	PT100P01/PT500GA1
Input control method	8-bit parallel (modified Centronics) Serial (TTL level)
Character type	222-IBM compatible 126-Japanese kana
Dimensions (WxDxH) mm	70.0 x 100.0 x 12.0
Weight (g)	40
Operating voltage (Vcc)	-5 VDC \pm 0.5
Current consumption (Icc)	Max. 20 mA @ 5 VDC (standby) Max. 200 mA @ 5 VDC (printing)
Operating temperature (°C)	-5 to 50
Storage temperature (°C)	-20 to 60
Model	PT100P01 / PT101P01
Applicable mechanism	All LTP1245 Series
Package form	80-pin flat package
Dimensions (WxDxH) mm	22.8 x 16.8 x 3.05
Configuration	C-MOS LSI
Input method	8-bit parallel (Centronics), Asynchronous serial
Operating voltage (Vcc)	5 VDC \pm 0.5
Operating frequency (MHz)	16 \pm 0.5%
Remarks	Use these CPUs and a gate array (PT500GA1) as a pair PT101P01 for use with auto cutter PT120P01 for use w/o gate array
Model	ACU6205A/B
Cut Method	Circular cutter type
Cut width (mm)	58 mm
Cut condition	full cut / partial cut
Drive voltage (VDC)	Motor 4.2V to 6.0V Detector 5V \pm 10%
Starting current (A)	1.2A max.
Operating time (ms/cycle)	0.6 sec. (max.) at 6.0 V
Cut frequency (cuts/minute)	30 max.
Life (cuts)	300,000 (M.C.B.F.)
Dimensions (WxDxH) mm	81.9 x 54 x 12
Weight (g)	50
Operating temperature (°C)	0 to 50
Storage temperature (°C)	-20 to 60
Paper thickness (mm)	75

Thermal Printers
Auto paper loading function

深圳市郁金香电子-微型打印机芯，微型打印组件，配件

深圳市福田区郁金香电子经营部

printer mechanism 打印机芯

门市部：深圳市福田区中航路都会100电子商城4楼4C113

电话TEL：+86 755 83662036

传真Fax：+86 755 22638877

Tel：(+86)0755-83956982

83662036

Fax：(+86) (0755)22638877

手机：13798497616

MSN：sz_lkj@hotmail.com